

7-STAR[★]

7-STAR[★]

**H.265 5MP POE NVR with VGA +1ch HDMI output ,
CCTV Onvif 5mp/3mp/2mp 8CH IEEE802.3Af
1080P Network Recorder P2P POE NVR**



Manual



AEeye

7-STAR[★]



App:AEeye



Manual

Main Features: Login PW:888888

Support H.265 dual stream video input 1-port SATA HDD interface inside, support max 6TB 3.5" Per HDD. 8 ports PoE power supply IEEE802.3af Global standard, support PoE camera/PoE splitter.

HDMI/VGA monitoring output: 1080P full HD, multi-channel mixed split screen, automatic main/sub stream preview Support camera Motion detection alarm signal input control recording(need camera support).

P2P technology: Support IOS/Android APP remote view.

Adopt HDD sequence writing method and the data is written from 0 track which increase 2.5X lifetime of the HDD Support ONVIF protocol, support multi-brand IP camera.

CMS PC software view.

support 4 screen the main circulation preview, synchronous playback support 4ch Provide network centralized monitoring management software.

1, Preview images freely exchange, image position changes, physical address, convenient construction;

2, Can drag the tree menu, man-machine dialogue more directly, it is more convenient to set parameters;

3, Electronic amplifier, the mouse roller can realize 15 times images can be arbitrary drag (preview, playback);

4, Instant screen shots and can check directly, the screen shots are saved independent regional preservation in the hard disk;

5, Video playback time column display, video type with that color, video query is very convenient;

6, Video backup according to time and length of time to backup, backup can be accurate to seconds (backup accurate);

7, U disk backup file can be directly on the host playback query, provide more convenience for playback backup file;

8, The resolution of the standard, the resolution can be adjusted according to the display device, give full play to display the image effect;

9, Hard disk sequence writing, starting with zero track writing data, can improve efficiency of hard disk 2.5 times.

7-STAR[★]

Specifications:



Product Model		NVR 5180 8ch POE NVR
Operating System		Embedded LINUX operating system
Image Code Control		Image code quality adjustable, variable bitstream optional
Dual Stream		Each channel can set main stream and sub stream.
Video Standard		1080P(1920X1080)30fps/960P(1280x960),720(1280x720)30fps
Monitoring Image Quality		1080P(1920X1080)/960P(1280x960)/720(1280x720)
Image Motion Detection		Each screen can set multiple detection areas and set 6-level sensitivity(IPC Supports)
Recording Playback Quality		1/4/8ch playback simultaneously
Region Cover Settings		Every channel can set 4 cover regions (IPC Supports)
Recording Mode		Support manual, auto, motion detection, alarm trigger record mode(Partly needs IPC Supports)
Backup Way		Support U disk, USB mobile HDD, USB DVD-RW, network storage and backup
Operation Way		Mouse
Local Login		User name and password.
Recording Storage		Local HDD, network
External ports	Video Input	1) 8x(1280x960)+sub[720x576]+4Ref.+9Play 8ch 1.3MP IP Camera 2) 8x(2048x1536)+sub[960x576]+4Ref.+4Play 8ch 3.0MP IP Camera 3) 8x(2592x1944)+sub[960x576]+4Ref.+4Play 8ch 5.0MP IP Camera
	Audio Input	8ch network audio input
	Video Output	1ch HDMI+1ch VGA
	Audio Output	1ch RCA
	Network Port	1 RJ45,10M/100M/1000M self-adaptive LAN port
	USB Port	2xUSB 2.0 ports
HDD	HDD Port	1XSATA Ports
	Max Capacity	MAX 6TB HDD
	POE Port	8 10/100M Independent LAN port,data transferring and power supply both by network cable,IEEE802.3af
	Input Consumption	120W
Mobile Surveillance		Support(iPhone, Windows Mobile, Black Berry, Symbian,Android) smart phone
Power Supply		DC48V2.5A
Power Consumption		≤70W(without HDD)
Working Temperature		-10° C ~ +55° C
Working Humidity		10%-90%
Dimension		Equipment: 260mmx220mmx43mm
Weight(without HDD)		N.W.: 1.6Kg
Installation Way		Desktop Installation

7-STAR[★]

7-STAR[★]



7-STAR[★]

7-STAR[★]

7-STAR[★]

7-STAR[★]

POE CCTV System Connection

Upper layer switch



IEEE802.3AF Power Supply

Max 80M-100M



Only 1 cable



**NVR Built in a 8 way
POE Power Switch**

POE Splitter

DC12V~1A Output



POE Camera (POE module inside)

Normal Camera (need power adapter)

7-STAR[★]

8ch HD POE-NVR

Support 8ch IP Camera Input

H.265



Excellent playback

Smooth playback screen, the picture is clear, and on-site environmental quality is almost the same, to support multi-channel playback, and local amplification, fixed playback, drag the progress, simple playback interface operation.

Not included HDD

7-STAR[★]

Support network monitoring, remote playback, remote video and control the NVR menu



Motion Detection


Support Multi-motion detection, trigger record/Alarm



7-STAR[★]

Onvif Protocol

Support onvif protocol, compatible with multi-brand ip camera



HDMI & VGA Monitoring output

Multi-channel mixed split screen output, up to 4K hd image resolution

