



SINSENG COMPONENTS PTE LTD

10 Jalan Besar #01-11 Sim Lim Tower


Singapore 208787

Tel: 6299 6868 Website: www.sinseng.com.sg

Est Since: 1971

HIKVISION

DS-K1T331W



Face recognition terminal



Value Series Face Access Terminal

- Face recognition terminal
- 3.97-inch touch screen, 2 Mega pixel wide-angle lens
- Deep learning algorithm
- 300 faces, 150,000 events storage
- TCP/IP, Wi-Fi(optional) communication, IP65
- Anti-spoofing detection
- Multiple time attendance status
- Face Recognition Accuracy Rate > 99%
- Face Recognition Duration(1:N) ≤ 0.2s
- Face Recognition Distance: 0.3m ~ 1m

DS-K1T331 Series Face Recognition Terminal

DS-K1T331 series face recognition terminal adopts deep learning algorithm, which helps to recognize the face faster with higher accuracy. It also supports multiple authentication modes: face authentication, etc. When installed on the turnstile, it can be applied in multiple scenarios, such as buildings, enterprises, financial industries, and other important areas.



Available Model

- DS-K1T331
- DS-K1T331W

Features

- 3.97-inch touch screen
- 2 MP wide-angle dual-lens
- Face anti-spoofing
- Face recognition distance: 0.3 m to 1.5 m
- Deep learning algorithm
- 300 face capacity, 1,500 card capacity (when connecting external card reader); 150,000 event capacity, and up to 20,000 captured pictures storage
- Face recognition duration < 0.2 s/User; face recognition accuracy rate ≥ 99%
- Capture linkage and captured pictures storage
- Transmits card and user data from or to the client software via TCP/IP protocol and saves the data on the client software
- Imports pictures from the USB flash drive to the device or export pictures, events, from the device to the USB flash drive
- Stand-alone operation
- Manage, search and set device data after logging in the device locally
- Connects to one external card reader via RS-485 protocol
- Connects to secure door control unit via RS-485 protocol to avoid the door opening when the terminal is destroyed




- Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out
- Supports multiple languages: English, Spanish, and Arabic
- *Biometric recognition products are not 100% applicable to anti-spoofing environments. If you require a higher security level, use multiple authentication modes*

Specifications

Model	DS-K1T331	DS-K1T331W
Operating system	Linux	
Screen	3.97-inch touch screen	
Card capacity (when connecting external card reader)	1,500	
Event capacity	150,000	
Face capacity	300	
Face recognition distance	0.3 m to 1.5 m	
Face recognition duration	< 0.2 s	
Network interface	10/100 Mbps, self-adaptive	
Camera	2 MP dual-lens camera with wide dynamic range	
Communication	TCP/IP	TCP/IP, Wi-Fi
Interface	USB × 1, electric lock × 1, door contact × 1, tamper × 1, exit button × 1, RS-485 × 1	
Power supply	12 V, 1.5 A, 18 W	
Working humidity	10 to 90% (no condensing)	
Working temperature	-10 °C to +50 °C (14 °F to +122 °F)	
Application environment	Indoor use	
Dimension (W × H × D)	120 mm × 110 mm × 23 mm (4.7" × 4.3" × 0.9")	

- *Exposing the equipment to direct sun light, low ventilation or heat source such as heater or radiator is forbidden (ignorance can cause fire danger).*

Dimensions


Distributed by


HIKVISION
Headquarters

No.55 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-800-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-29469900
sales@pramathikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6602
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Lat.am.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikis.psnfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432050
sales.me@hikvision.com

Hikvision Singapore
T +65-6884-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-3238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2153-1761
info.hk@hikvision.com

Hikvision Russia
T +7-465-609-07-99
saleru@hikvision.com

Hikvision Korea
T +82-1031-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com