

7-STAR^{*}

RFID Entry Door Access Control System



20C

7-STAR[★]



7-STAR[★]



7-STAR[★]



7-STAR^{*}



7-STAR[★]



7-STAR[★]



7-STAR^{*}

Features:

Standalone, single door control

Low Priced, connect an electric strike and power supply and you're done

No Control Panels Standalone Access Controller

Easy and simple to use

Has a flat back so it's easy to install on any flat surface

Operating Mode Card only Keypad only Card with Keypad

Card capacity is 250 users

Programmable door release time 1-250 seconds

Access code can be added or deleted by keypad management

Built-in electric buzzer for audible card entry and programming

Data is protected even after power failure

Machined housing in high durable.

EM-ID thin card or key fob optional

Specifications

Operating voltage: dc 12 V

Unlock current: $\leq 1000\text{ma}$

Static current: $\leq 60\text{ mA}$

Memory: 250 standard users

Card size: 0-10 cm

RF type: EM Card, Keychains

Operating temperature: $-10 \sim 70\text{ s}$

Wide Rel. Humidity range: from 10 to 90%

Opening doors options (Admin-user Selectable): card (tag key) & password / card (tag key) only / password only

Product size: 11.7 * 11.7 * 2.1 cm

Product weight: 134 g

Size Package: 13.5 * 11.8 * 2.2 cm

Package Weight: 210 g