


7-STAR[★]

Full-HD Hybrid 16 Channel Digital Video Recorder



7-STAR[★]

- H.264 video compression, 1080 p / 720 p / 960 H resolution HD, VGA & HDMI output.
- 720 p / 960 H / 1080 p
- 16 video in ports, 2 audio in / 1ch audio output + 2 pcs USB port
- P2P (cloud), no longer needs a port for the remote monitor.
- Smartphone, PC remote control. Application name: xmeve
- Motion detection and email alert
- Support multi languages English, Russian, Italian, Portuguese, Spanish, French, German. etc ..
- 6 in 1 Support for AHD / CVBS / TVI / CVI / XVI / IP cameras
- Motion detection and email alert / registration
- Support ONVIF



7-STAR[★]

Specification:

	Model	DVR1611L/ 16CH
System	Main processor	Technical grade embedded microprocessor
	Operating system	Embedded LINUX operating system
	System resource	Multi-channel real-time recording synchronously, multi-channel real-time playback, multi-channel multi-user network operation,USB back up.
Interface	Operation interface	16bit real color GUI interface support mouse operation
	Display screen	1/4/8/9/16 screen (take analog channel as an example, other is base on the selected channel mode)
Video	Video standard	PAL/NTSC(720P)
	Image encode	H.264(High Profile); JPEG
	Monitor quality	Monitor: D1,VGA,HDMI:High definition Support:1920*1080/1280*720/1440*900/1280*1024/1024*768/800*600)
	Playback quality	1080P/ 720P/D1/CIF
	Encode capability	16*1080P(12FPS)
	Decode capability	16*1080P(12FPS)
	Multi-mode video input	AHD: 16*1080NH(12FPS); HVR: 8*1080P(AHD)+8*960P(IP) NVR: 8*1080P/8*960P/4*3MP
	Motion detection	Each channel can set 192(16*12)detection area: can set multi-level of flexibility (for local analog channel only)
Audio	Audio compression	G711A
	Bidirectional talk	Support
Record and playback	Record mode	Manual>alarm>motion detection>timing
	Local playback	1/4/8/9/16ch playback synchronously (take local analog input for example, other is depended on the selected channel mode)
	Video search	Time/date/event/channel search
Storage and back up	Space occupatiorn	Video: CIF 4-5G/day*channel,D1 16-20G/day*channel;720p 10G/day*channel Audio:691.2M/day*channel
	Video storage	Local HDD/Network
	Back up mode	Network backup/USB portable HDD/USB imprint/SATA imprint
Interface	Video input	16CH BNC(1.0Vp-p,75ohm)
	Video output	1CH VGA, 1CH HDMI
	Audio input	2CH RCA
	Audio output	1CH RCA 200-3000mV,5K ohm)
	Alarm input	N/A
	Alarm output	N/A
	Network port	RJ45 10M/100M self-adaptive Ethernet port
	PTZ control	NO PTZ
	USB port	2*USB2.0
	HDD port	1 SATA ports
other	Power	12V/2A
	Consumption	<15W (not including HDD)
	Temperature	-20+55
	Humidity	10%-90%
	Atmosphere pressure	86kpa-106kpa
	Dimension	L255*W 235*H45MM