

SINSENG COMPONENTS PTE LTD

Jalan Besar #01-11 Sim Lim Tower, Singapore 208787 Tel:6299 6868 Fax:6299 1919 Email:ss6868@singnet.com.sg www.sinseng.com.sg

Mon-Sat:9.30am-6.30pm Sunday:11.30pm-4.30pm



Vstarcam HD 16CH NVR Audio input HDMI 16 Channel Network Video Recorder


















Fluent and clear video playback, support multi-channel synchronized playback, timed playback, progress drag.





Multi-channel view

Support different channel pre-view and playback.



TARCAM® Three working modes optional

2MP 1920x1080P

Mode I

25 FPS: Sixteen 2MP cameras working simultaneously, and support Four 2MP cameras playback



Mode II

25 FPS: Sixteen 3MP cameras working simultaneously, and support One 3MP camera playback



5MP 2592*1944P

Mode III

25 FPS: Four 5MP cameras + Twelve 2MP cameras working simultaneously, and support One 5MP camera playback

Dual-stream design

Network surveillance quality and local surveillance quality can be set individually, local storage use main stream, smartphone, PC remotely view useing sub stream.









Plug&Play

Plug and Play technology applied, eliminate cabling work.




Up to 6TB Local Storage

Select from 1TB to 6TB built-in storage so that your videos can be stored locally and securely.







Audio and video output

Video and audio surveillance





16 Channel Network Video Recorder

Supports H.265+/H.265/H.264 • HDMI/VGA Output Supports 5-Megapixel Cameras







Shop



Supermarket



Building



Records More Images with Less Storage

The N8216 provides faster video streaming and stores more footage than ever thanks to H.265+/H.265 video compression technology.



H.264 video compression technology

Required storage space: 100%

Required bandwidth: 100%

H.265+/H.265 video compression technology

Required storage space: 50%

Required bandwidth: 50%



Captures Details Beautifully

Support HDMI and VGA output; The output resolution is up to1080P(HDMI & VGA);

And support the maximum HD video streaming of 5 megapixel

camera view and playback



Backup for important Recording

Support backup by USB & Network, can easy to backup to USB disk or Mobile Hard Disk.

















Alarm log cloud storage

Support Baidu, Google, Dropbox network disk storage






model		N8216-2
Video input	IP video input	16 CH 720P / 960P / 1080P, RJ45 interface
	switch	None
Video encoding	HDMI output	1 CH, HDMI output; Resolution: 1920 x 1080 1080P / 60Hz;
	VGA output	1 CH, VGA output; Resolution: 1920 × 1080 / 60Hz
	Audio output	HDMI audio output, 3.5mm audio port output for optional
Video encoding	Video compression	Stander H.265, H.
	Recording / playback	16CH 1080 720p record, 2CH 1080 playback
	Video resolution	720P, 960P, 1080 720p record
	frame rate	PAL: 25 F / s; NTSC: 30 F / S
	Video bit rate	256 Kbps-2.0 Mbps (@ 1080)
	Stream type	Audio / Video, Variable Rate (VBR), Bit Rate (CBR)
	Dul stream	Supprt
	Audio compression	G.711
	stream	70 150mbps
HDD	Storage type	1 * SATA
	Storage capacity	Up to 6 terabytes
	backup	USB backup, remote backup
External interface	Network interface	RJ45 10M / 100M Internet interface
	USB interface	2 * USB2.0 interface (support upgrade, backup, mouse)
	Serial interface	1 * RS485 interface
other	temperature	-10 ° 55 °
	size	TBD
	weight	TBD
	Operation system	Embedded Linux operating system
	Soft power off	Not supported
	Device control	Infrared remote control, mouse
	Power input	DC + 12 V / 2A



Packing List







NVR



Mouse



Screw

Certificate



Shenzhen VStarcam Technology Co., Ltd.

Authorization Certificate

Authorize:

Sinseng Components Pte Ltd

As VStarcam's Distributor in Singapore

who shall have the rights to sell the VStarcam's smart home products with VStarcam Brand.

Period: 1st, November, 2019 to 1st November 1, 2020

Authorized by

Shenzhen VStarcam Technology Co., 1td.

Issue date: 1" November, 2019

www.vstaream.com